



FEATURES

- CRI>90 LED panel suitable for standard ceiling grid
- Aluminum body with PMMA diffuser
- Powder coated finish
- Non-dimmable flicker –free driver included
- ICF-rated and can be abutted and covered with insulation
- IP20 indoor use only
- Dimmable options: TRIAC, 1-10V, DALI
- Customized colours and IP54/IP66 versions upon request
- Five- year warranty

TECHNICAL SPECS

Item No.	Size	Power	Lumen Output	CRI	Colour Temp	Dimmable
BCP0664	595x595	36	3400lm	>90Ra	4000K	Non-Dim
BCP0665	595x595	36	3400lm	>90Ra	5000K	Non-Dim
BCP0666	595x595	36	3400lm	>90Ra	6000K	Non-Dim
BCP1234	1195x295	36	3400lm	>90Ra	4000K	Non-Dim
BCP1235	1195x295	36	3400lm	>90Ra	5000K	Non-Dim
BCP1236	1195x295	36	3400lm	>90Ra	6000K	Non-Dim
BCP1264	1195x595	60	6100lm	>90Ra	4000K	Non-Dim
BCP1265	1195x595	60	6100lm	>90Ra	5000K	Non-Dim
BCP1266	1195x595	60	6100lm	>90Ra	6000K	Non-Dim