

THREE PHASE TRACK LIGHT



FEATURES

- Three phase LED track light
- Aluminum body
- Powder coated finish
- Constant current LED driver fitted
- 350° rotatable 90° adjustable head
- CRI 90
- Colour option: White & Black
- Ta: -20°C to +40°C
- Suitable for Residential and Commercial Area
- Anti-glare honeycomb is available

TECHNICAL SPECS

| Item No. | Power | Lumen Output | CRI | Colour Temp | Beam Angle | Colour | Dimmable |
|------------|-------|-----------------|-------|-----------------|---------------|----------------|----------|
| LR1003R-02 | 15 | 1350lm | >90Ra | 4000K | 38° | Black or White | Non-dim |
| LR1005R-02 | 33 | 2970lm | >90Ra | 4000K/300 0K | 38° | Black or White | Non-dim |



THREE PHASE TRACK LIGHT



FEATURES

- Three phase LED track light
- Aluminum body
- Powder coated finish
- Constant current LED driver fitted
- 350° rotatable 90° adjustable head
- CRI 90
- Colour option: White & Black
- Ta: -20°C to +40°C
- Suitable for Residential and Commercial Area
- Anti-glare honeycomb is available

TECHNICAL SPECS

| Item No. | Power | Lumen Output | CRI | Colour Temp | Beam Angle | Colour | Dimmable |
|------------|-------|-----------------|-------|----------------|---------------|----------------|----------|
| LR1003R-02 | 15 | 1350lm | >90Ra | 4000K | 38° | Black or White | Non-dim |
| LR1005R-02 | 33 | 2970lm | >90Ra | 4000K | 38° | Black or White | Non-dim |
| 10053P3KBK | 33 | 2970lm | >90Ra | 3000K | 38° | Black | Non-dim |
| 10053P3KWH | 33 | 2970lm | >90Ra | 3000K | 38° | White | Non-dim |